

TITLE

Marine Vessel Lifting System with Variable Level Detection

RELATED APPLICATIONS

This application claims priority of March 19, 2003, the filing date of Provisional Application No. 60/455,927.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a system for positioning a cradle for lowering and lifting a marine vessel relative to the height of the surface of a water body, especially when the height of the water body fluctuates over time, as with tidal action, and discounts the height of the water body as it relates to wave action.

Background of the Invention

Boat lifts and davits are well known to those who are skilled in the art. Parkins et al, U.S. Patent No. 5,769,568, describes one of the more common layouts for a lifting cradle used to lift a marine vessel. When lifting or lowering a marine vessel, the operator typically must depress a control button, either remotely or while at the motor controls, and keep this button depressed until the proper level of the cradle has been achieved.

Recently those skilled in the art have added limit switches, or other sensors, to the motors to terminate the motors when the proper, fixed position has been achieved. However, the operator must still keep the control button depressed until the final desired position is achieved.

In regions where periodic and continuous changes in the water surface level is

1 common, such as by tides or in rivers, these pre-defined and fixed positions will not  
2 allow the marine vessel to launch or to be retrieved unless precise conditions are met.

3 Endres et al, U.S. Patent No. 5,593,247, describe a boat lift control system in  
4 which a plurality of elevations may be preprogrammed into the system corresponding to,  
5 for example, low tide, high tide, etc. The system is activated by a button, designated as  
6 'up' or 'down', and moves the lifting cradle to the next higher, or lower, position than the  
7 starting point, respectively, which may not be the desired position. The system is  
8 activated again and the lifting cradle continues on to the next preprogrammed position.  
9 This process continues until the desired position of the lifting cradle is achieved.

10 However, these preprogrammed states are not always useful. A typical situation  
11 would involve an outgoing tide, which results in a water surface level between two of the  
12 preprogrammed states. Use of the preprogrammed states would result in the lift either  
13 being too high or excessively low for efficient loading, launching or retrieving of the  
14 vessel.

15 Water level sensors are well known to those skilled in the art. Most often a  
16 water level sensor is developed and used to simply report when a given depth of water  
17 has been achieved and signals this condition to the user. Barrows, U.S. Patent No.  
18 5,515,025, and Jones, U.S. Patent No. 3,995,251, describe water level sensors that  
19 determine the level of water relative to the boat trailer and then provide a signal to the  
20 user. However, these inventions are, admittedly, biased by wave action and changes to  
21 the angle of inclination of the trailer. Either of these situations could result in the marine  
22 vessel not seating properly and not providing the desired loading/launching/retrieving  
23 effect.

1     SUMMARY OF THE INVENTION

2             Therefore, it is an objective of the present invention to provide a marine vessel  
3     lifting system that automatically, through a remote control and/or electrical switches,  
4     delivers the lifting cradle to the proper position relative to the waterline of the vessel.

5             It is another objective of this invention to provide a lifting system which performs  
6     these functions regardless of the water surface level or the degree of wave action of the  
7     water body and during times when there is inadequate lighting to determine the cradle's  
8     position relative to the water's surface.

9     BRIEF DESCRIPTION OF THE DRAWINGS

10            FIG. 1 is a control system schematic for a marine vessel lifting system with variable  
11     level detection in accordance with an embodiment of the present invention;

12            FIG. 2 is an elevation view of the marine vessel lifting system mounted to a  
13     conventional boat lift frame;

14            FIG. 3 is a flow diagram of the "Storage" position control function of the system;

15            FIG. 4 is a flow diagram of the "Load/Unload" position control function of the  
16     system; and

17            FIG. 5 is a flow diagram of the "Launch/Retrieve" position control function of the  
18     system.

19  
20     DETAILED DESCRIPTION

21            The present invention relates to a marine vessel lifting system 10 that detects  
22     its current state position and responds accordingly to achieve a new desired state. The

1 preferred embodiment of this invention mounts a portion of the level-sensing module 11  
2 to the lifting cradle 12 at a position that corresponds to the waterline 13 of the vessel 60.  
3 The receiver module 14 and motor control module 15 are mounted to the lifting structure  
4 and are energized via the local electrical power source. The motors 16 are mounted in a  
5 manner typical of the lifting mechanism. In Fig. 2, a lifting mechanism is shown  
6 mounted on pilings P, including horizontal cradle frames 50 and upper frames 51, one  
7 on each side of the vessel 60. Cross members (not shown) span the distance between  
8 the cradle frames 50 to support the weight of the vessel and/or to maintain interval.  
9 Vertical guides 52 are mounted on the cradle frames to align the vessel 60  
10 with the cradle when the cradle is submerged and to act as fenders as the cradle is  
11 raised. The level-sensing module 11 is movably connected to one of the vertical guides  
12 52 in a manner to be adjusted to the desired height corresponding to the vessel  
13 waterline 13, when in the cradle. The motors 16 turn pulleys, cranks, worm gears or  
14 other devices to shorten the distance between the cradle frames and the support beams  
15 51 to vertically move the vessel. As shown, pulleys 54 are mounted on the cradle  
16 frames 50 and rotate as cables, ropes, chains, etc. 53 move between motor drive  
17 mechanisms and the terminal ends 55 to lift and lower the vessel 60. The operator  
18 typically holds the transmitter 70, so its location varies.

19 In the preferred embodiment the system is aware by various switch positions  
20 but without the use of EPROMs or other memory or programming means, of at least  
21 three distinct states that are known to vary over time. These distinct states are vessel  
22 storage, vessel load/unload and vessel launch/retrieve. While the wiring and status of  
23 the various inter-related switches and circuits is specified below, these are preferred,  
24 and it is recognized that wiring and status of the inter-related circuits and switches could  
25 be executed differently with the same result and such combinations and permutations  
26 are included.

1 As shown in Fig. 1, the transmitter module has at least three buttons 71, 72, and 73,  
2 with each button a part of a separate but related electrical circuit. To aid the operator  
3 during night-time operation, these buttons may be illuminated. The illumination may be  
4 by LED, incandescent, or other device. The buttons may be labeled verbally or  
5 pictograph to indicate the modes of operation. For example, one of the buttons may  
6 have a depiction of an arrow pointed in one direction and another button with an arrow  
7 pointed in the opposite direction and the third button may be labeled AUTO. Or the  
8 buttons may have the terms storage, launch/retrieve, and load/unload labeled on the  
9 transmitter module. There may be more than three buttons on the transmitter, eg., five,  
10 to perform all the functions desired.

11 In one example, when directed to attain the vessel storage position, either  
12 through a button 71 pushed and released remotely or locally, the system sends a signal  
13 to the level-sensing module 11. At the level-sensing module 11 the signal is either  
14 terminated, corresponding to the condition that the cradle 12 is already in the stored  
15 position and the storage limit switch is closed or, if the limit switch is open, the level-  
16 sensing module signal is latched, thereby sending a signal to the motor control module  
17 15 for the motors 16 to begin lifting the cradle 12. The motors 16 initialize a signal to the  
18 visual indicator that they are energized. This initial signal is held until the cradle 12  
19 reaches the storage position, whereby the signal is terminated causing the motors 16 to  
20 stop and the visual signal to extinguish.

21 In the preferred embodiment, the level-sensing module 11 is located apart from  
22 the load/unload sensor and the launch/retrieve sensor and utilizes mercury switches to  
23 discern if the position of the lifting cradle 12 is in the storage position. Mercury switches  
24 are reliable devices in any environment and are not prone to erroneous readings caused  
25 by rain splashing and corrosion, like many other sensors would be.

26 In an alternate embodiment, the use of limit switches, counting switches, or

1 timing devices, or encoders may be used to provide the position of the lifting cradle 12 in  
2 a storage or other position relative to the vessel's waterline 13. An alternate  
3 embodiment may also integrate the storage, load/unload, and launch/retrieve sensors  
4 into a single unit.

5 In another example, when directed to launch or retrieve the vessel 60, either  
6 through a button 72 pushed and released remotely or locally, the launch/retrieve circuit  
7 sends a signal to the level-sensing module 11. At the level sensing module 11 the signal  
8 is either terminated, corresponding to the condition that the cradle is already in position  
9 to launch/retrieve the vessel, or latched sending another signal to the motor control  
10 module for the motors to begin moving the cradle. The motors 16 initialize a signal to the  
11 visual indicator that they are energized. This initial signal is held until the cradle reaches  
12 the launch/retrieve position, whereby the signal is terminated causing the motors to stop  
13 and the visual signal to extinguish.

14 In yet another example, when directed to load or unload the vessel, either  
15 through a button 73 pushed and released remotely or locally, that circuit sends a signal  
16 through the load/unload circuit to the level-sensing module. At the level sensing module  
17 11 the signal is either terminated, corresponding to the condition that the cradle is  
18 already in position to load/unload the vessel, or latched sending either a signal to the  
19 motor control module for the motors to begin moving the cradle, as required. The motors  
20 initialize a signal to the visual indicator that they are energized. This initial signal is held  
21 until the cradle reaches the load/unload position, whereby the signal is terminated  
22 causing the motors to stop and the visual signal to extinguish.

23 It is important to note at this point that the launch/retrieve and the load/unload  
24 positions for the vessel are most often variable. In tidal regions these positions may  
25 change by as much as 2-5 ft. during the course of a 24 hour period. In addition, some  
26 regions have multiple high and low tides in a day's time. This makes automating a

1 system more difficult. Therefore, the launch/retrieve and load/unload positions must  
2 always be measured relative to the waterline of the vessel and not fixed according to the  
3 support structure of the boat lift or davit. There may be another command or position for  
4 the boat lift to compensate for higher than normal water levels in storms.

5 In the preferred embodiment the level sensing module utilizes float switches to  
6 discern the position of the lifting cradle relative to the vessel's waterline. Float switches  
7 are reliable devices in a liquid environment and are not prone to erroneous readings,  
8 caused by rain or splashing, like a moisture sensor, water soluble disc, or porous paper  
9 fuse link would be.

10 At night it is not easy to discern whether or not the lifting cradle is in motion.  
11 Therefore, it would be valuable to observe, through a visual signal, that the lifting cradle  
12 is in motion following the instruction to move to a new state. However, alternate  
13 embodiments may utilize other types indicators to achieve the same results.

14 Finally, the operator can bypass the level sensing module, and each of these  
15 three states, by pushing and holding a button, either remotely or locally, thereby  
16 causing the motors to begin raising the cradle. Similarly, the operator can push and hold  
17 a different button, either remotely or locally, causing the motors to begin lowering the  
18 cradle. In this manner the buttons act as momentary switches.

19 As an alternate embodiment the bypass conditions can be set to latch. Configured  
20 as such the operator would push and release the button, the motors would operate in their  
21 respective directions, and the operator would push and release the button a second time  
22 to disengage the motors.

23 To prevent damage to the boat lift or davit structure, typically caused by the  
24 failure of the level sensing module to sense the storage level and disengage the motors,  
25 the preferred embodiment of this invention utilizes a pair of mercury switches which  
26 serve to energize the motor control module. In the event the mercury switches are

1 tripped the motor control module will not accept signals from the level sensing module  
2 and the lifting motors will not engage. Mercury type switches are preferred for their  
3 simplistic nature and high reliability and a pair of switches is used for redundancy.  
4 However, alternate embodiments may utilize other types and numbers of switches to  
5 achieve the same results.

6 A number of embodiments of the present invention have been described.  
7 Nevertheless, it will be understood that various modifications may be made without  
8 departing from the spirit and scope of the invention. Accordingly, it is to be understood  
9 that the invention is not to be limited by the specific illustrated embodiment but only by  
10 the scope of the appended claims.